

Closed cooling
system

Elektravägen 53
SE-126 30 Hägersten, Sweden
+46 10 252 30 00
www.ozonetech.com

Closed cooling system WBK 5650s/1550/2380s

These cooling systems are the perfect solution for situations where cooling water is not available and/or cost of cooling water consumption is too high.

The system has a cover of stainless steel (SS 304) containing a PE tank isolated with XPS. The cooler is equipped with safety devices for overcurrent, low-level and high pressure. For fault indication there is a signal lamp and potential free contact applied. The controlling is done by an electronic controller with readout.

These cooling systems can also be re-designed and customized to any specific flow and pressure requirements.



Technical specification

	WBK5650s/1550	WBK2380s
Dimensions (WxDxH)	450 x 490 x 720 mm	520 x 520 x 870 mm
Weight (empty)	42 kg	60 kg
Power supply	230 V / 50 Hz	230 V / 50Hz
Power requirement (5/50°C)	650 W	975 W
Cooling capacity (5/50°C)	1280 W	1950 W
Capacity (l/h) ΔT10K	110 l/h	165 l/h
Ambient temp. (max)	32 °C	35 °C
Refrigerant	R134a	R134a
Tank capacity (gross)	50 l	80 l



© Ozonetech

ozonetech.
a MELLIFIQ brand